

VB Burner Series







VB Burner Series Design features



1. Accessory Exclusion Zone

Elevated lip around the burner mouth that stops accessories from sitting over the flame or blocking the shut off procedure. This raised lip includes air holes that allows air to flow smoothly around the fuel to achieve a better flame within the setting.

2. Height Adjustable

Adjustable feet level and lift the burner to the best setting depending on the depth of the grill it's being placed within.

High Quality

Crafted from high quality, 304 grade stainless steel inside and out, our burners are built to last a lifetime.

3. Dedicated Filling Point

A designated, inbuilt filling point to ensure the same procedures can be followed to decrease the likelihood of overfilling.

Easy Installation

The VB2 burner has several layers of internal features that increases its efficiency including vertical baffles, aspiration vents and dense padding - all of which is built to last a lifetime.

Dual Purpose Lid

A simple lid is used to extinguish the flame and cover the burner opening when it is not in use. This prevents dust from falling into the tank, leaving it clean and safe for use year round.



4. Colour

Available in Black.

VB2 is finished in Black Ceramic Coating, designed to blend with existing fireplaces.

Clean Burning

Warm your home, not the planet. Powered by e-NRG bioethanol, a sustainable plantbased fuel, VB2 produces no smoke, no soot, and no mess.

No Flue, No Chimney, No Vent No vent or flue required, which

stops heat from escaping. Increase heat output by closing the dampener or sealing off the flue with a metal plate.

Available in 1 Size

The VB2 holds 2 Litres of environmentally-friendly e-NRG bioethanol fuel, providing a flame that burns for up to 6 hours.

*Decorative media is not to be placed

Included Accessories



Jerry Can with Safety Spout & e-NRG bottle adaptor



Lighting Rod & Lighter

Optional Accessories



Black Glass Charcoal*



directly on top of the burner or anywhere they can interfere with the operation of the burner or the stability of flame.



VB2 Specifications

Specially created for easy integration into existing fireplaces. A simple and effective way to create a new, modern fireplace.

Burner Ventilation and Efficiency*

















5						
Dimensions L x W x D mm/in	Fuel Capacity	Heats on Average (Indoors)	Fuel Consumption	Thermal Output Net (MAX)	Approx. Burn Time	Minimum Room Size (per burner)
330 x 110 x 112.5 13 x 4.3 x 4.4	2 L [0.5 Gals]	Over 15 m ² [161 ft ²]	0.5 L/h [0.13 Gal/h]	7.24 MJ/h 6,180 BTU/h 2.5 kW	6 hours	45 m³ [1,589 ft³]

Application	Indoor		
Burner Colours	Black ESF.B.VB2		
Materials	Grade 304 Stainless Steel Burner, with Black Ceramic Coating		
Approx. Weight	1.8kg [4lbs]		
Fuel Type	e-NRG Bioethanol / e-NRG.com		







Read the manual carefully before operating the burner.

A size template is available to test the burner fits the setting.

^{*}These values are indicative only and may vary depending on the model purchased, installation, and the seasonal resource used to manufacture e-NRG.